

### Dredging Steel Pipe



#### Technical Specifications

Standard	API 5L, API 5CT, ASTM A53, ASTM A252, EN10217, EN10219, DIN, JIS, BS
Outer Diameter	219.1—3048 mm or 8inch—120inch
Wall Thickness	5mm—30 mm or 0.196inch—1.181inch
Length	3—20 m
Packing	In bulk
Payment Term	T/T, L/C
Delivery Time	45 days after we received the deposit or the L/C
Other Services	Beveled / Plain end or vanished as per clients confirmation ; With or without caps as per customer's requirements, Fusion Bond Epoxy Coating, Coal Tar Epoxy, 3PE, Varnish coating, Bitumen coating, Black Oil coating as per customers requiremen
Material	API 5L GR.B, X42, X46, X56, X65, X70 ASTM A53 GRADE A, GRADE B EN:S275, S275JR, S355JRH, S355J2H
Usage	For linepipe in petroleum and natural gas , water and gas, mineral slurry. Also for chemical industry, building structure and pile driving, etc. Used for low pressure liquid delivery, such as water, gas, and oil.piling, dredging project,etc
Export to these Countries	Canada, USA, Peru, Chile, Colombia, Brazil, India, Malaysia, Singapore, Vietnamese, Australia, Myanmar, Kenya, South Africa, Spain, Italy, France, England, Belgium, etc
Certificates	API 5L , API 5CT, ISO ,CE,KS,etc



Dredging Steel Pipes in workshop

Testing equipment



Dredging Steel Pipes in factory



**Chongqing Hi-Sea Marine Equipment Import&Export Co.,Ltd.**

**Address:** 20-5,General Chamber of Commerce Building, No.2 Hongjin Street, Yubei District, Chongqing, China

**Email:** machine@hiseamarine.com mitang0708@foxmail.com **Skype:** cncqtang **QQ:** 2278612160

**TEL:** +86-23-67032301 **FAX:**+86-23-67955123 **Mobile:** +86-18108354610 **Post Code:**401147

**Website:** www.hiseamarine.com www.chinahisea.com