

Polythene Floater



Performance and Feature:

The dredging pipe is stuck with polythene floater outside, it is suitable for operation in high surge areas, with a character of low center of gravity, wave-resistance, impact-resistance, lower cost and safety for construction.

Technical specification

ID of Dredging pipe \varnothing (mm)	Thickness of pipe (mm)	ID of Float \varnothing (mm)	OD of Float \varnothing (mm)	Length of Float (mm)	Center Length of Float (mm)	End length of Float (mm)	Thickness of Polythene (mm)
350	6	380	1000	1000	600	200x2	5
414	6	430	1200	1200	700	250x2	6
450	8	480	1300	1300	800	250x2	6
500	8	530	1300	1400	840	250x2	7
550	10	580	1400	1500	900	300x2	7
600	10	630	1450	1650	1050	300x2	8
650	12	680	1500	1800	1200	300x2	8
700	12	730	1600	1900	1200	350x2	10
750	12	780	1700	1900	1200	350x2	10

800	16	830	1800	2000	1200	400x2	12
850	16	880	2000	2500	1500	500x2	12

- Note:**
1. Two pairs of float form one group, one pairs consist of two pieces. One group of float can support dredging pipe of 6 meters length.
 2. Other specification are available upon request.



Polythene Floater working picture

Chongqing Hi-Sea Marine Equipment Import&Export Co.,Ltd.

Address: 20-5,General Chamber of Commerce Building, No.2 Hongjin Street, Yubei District, Chongqing, China

Email: machine@hiseamarine.com mitang0708@foxmail.com **Skype:** cncqtang **QQ:** 2278612160

TEL: +86-23-67032301 **FAX:**+86-23-67955123 **Mobile:** +86-18108354610 **Post Code:**401147

Website: www.hiseamarine.com www.chinahisea.com