

单芯交联聚乙烯绝缘电力电缆

Single core XLPE insulated power cable

3.6/6kV

标称截面 Nominal cross sectional area mm ²	导体参考直径 Reference conductor diameter mm	绝缘标称厚度 Nominal insulation thickness mm	电缆近似外径 Approx overall diameter of cable mm	电缆近似重量 Approx weight of cable kg/km		电缆近似外径 Approx overall diameter of cable mm	电缆近似重量 Approx weight of cable kg/km		电缆近似外径 Approx overall diameter of cable mm	电缆近似重量 Approx weight of cable kg/km	
				YJV YJY	YJLV YJLY		YJV32 YJV33	YJLV32 YJLV33		YJV62 YJV63	YJLV62 YJLV63
25	6.0	2.5	19	420	270	26	1045	894	22	593	441
35	7.0	2.5	20	521	310	27	1170	960	23	706	496
50	8.2	2.5	21	670	370	28	1357	1055	24	869	566
70	9.9	2.5	23	885	460	30	1629	1199	26	1100	672
95	11.5	2.5	24	1138	554	31	1937	1352	28	1370	785
120	12.9	2.5	26	1370	642	33	2224	1496	29	1615	888
150	14.5	2.5	27	1657	749	35	2761	1853	31	1919	1011
185	16.1	2.5	29	1992	871	37	3179	2057	33	2670	1148
240	18.5	2.6	32	2566	1085	40	3841	2357	36	2871	1386
300	20.6	2.8	35	3171	1315	43	4561	2705	39	3052	1648
400	23.5	3.0	38	3982	1660	47	5899	3576	43	4713	2391
500	26.6	3.2	42	5044	2027	52	7150	4122	47	5863	2836
630	30.4	3.2	46	6260	2460	56	8614	4798	51	7173	3357
800	34.1	3.2	50	7824	2995	60	10375	5529	55	8832	3986

注：电缆近似重量为聚氯乙烯护套电缆重量
Note: The approx weight of cable is the weight of PVC sheathed cable.

三芯交联聚乙烯绝缘电力电缆

Three core XLPE insulated power cable

3.6/6kV

标称截面 Nominal cross sectional area mm ²	导体参考直径 Reference conductor diameter mm	绝缘标称厚度 Nominal insulation thickness mm	电缆近似外径 Approx overall diameter of cable mm	电缆近似重量 Approx weight of cable kg/km		电缆近似外径 Approx overall diameter of cable mm	电缆近似重量 Approx weight of cable kg/km		电缆近似外径 Approx overall diameter of cable mm	电缆近似重量 Approx weight of cable kg/km		电缆近似外径 Approx overall diameter of cable mm	电缆近似重量 Approx weight of cable kg/km	
				YJV YJY	YJLV YJLY		YJV22 YJV23	YJLV22 YJLV23		YJV32 YJV33	YJLV32 YJLV33		YJV42 YJV43	YJLV42 YJLV43
25	6.0	2.5	36	1623	1167	40	2174	1718	45	3215	2760	51	4844	4289
35	7.0	2.5	38	2042	1409	43	2641	2008	48	4116	3483	54	5401	4768
50	8.2	2.5	41	2602	1693	45	3241	2332	51	4819	3910	56	6189	5281
70	9.9	2.5	45	3332	2041	49	4044	2753	55	5753	4462	60	7170	5879
95	11.5	2.5	49	4223	2466	53	4988	3231	59	6833	5077	64	8399	6642
120	12.9	2.5	52	5040	2852	57	5894	3706	62	7877	5688	67	9490	7302
150	14.5	2.5	56	5994	3265	61	6923	4195	66	9039	6310	71	10800	8073
185	16.1	2.5	59	7129	3758	64	8115	4745	70	10326	6955	75	12075	8804
240	18.5	2.6	65	9050	4688	71	10153	5092	76	12549	8138	81	14481	10019
300	20.6	2.8	72	11101	5324	77	12324	6747	84	15872	10294	87	17122	11444
400	23.5	3.0	79	13831	6850	86	15871	8841	92	19165	12184	95	20488	13507
500	26.6	3.2	88	17393	8290	95	19669	10567	101	23334	14231	104	24756	15662

注：电缆近似重量为聚氯乙烯护套电缆重量
Note: The approx weight of cable is the weight of PVC sheathed cable.