

Specifications

| Model | | Cores | Nominal Area mm ² |
|----------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|----------------|---------------------------------|
| Copper | Aluminum | | |
| YJ(F)V-xx ZR-YJ(F)V-xx WDZ-YJ(F)E-xx WDZN-YJ(F)E-xx | YJ(F)LV-xx ZR-YJ(F)LV-xx WDZ-YJ(F)LE-xx | 1 ^a | 2.5~300 |
| | | 2 | 1.5~185 |
| | | 3 | 1.5~300 |
| | | 3+1, 4 | 4~300 |
| | | 5, 3+2, 4+1 | |
| YJ(F)V22-xx YJ(F)V32-xx ZR-YJ(F)V22-xx ZR-YJ(F)V32-xx WDZ-YJ(F)E23-xx WDZ-YJ(F)E33-xx WDZN-YJ(F)E23-xx WDZN-YJ(F)E33-xx | YJ(F)LV22-xx YJ(F)LV32-xx ZR-YJ(F)LV22-xx ZR-YJ(F)LV32-xx WDZ-YJ(F)LE23-xx WDZ-YJ(F)LE33-xx | 1 ^a | 10~300 |
| | | 2 | 4~185 |
| | | 3 | 4~300 |
| | | 3+1, 4 | 4~300 |
| | | 5, 3+2, 4+1 | |
| | | | |
| | | | |

^a : Non-magnetic material should be applied for single core cable armor

Note:-xx means conductor working temperature.90℃ and 105℃.90℃ omitted

For flame retardant cable,it can be divided into 4 type,Cate A,B,C,D.ZR- or Z- means ZC when user has no specific request.