

Multi purpose distribution cable GJFJV

Multi purpose distribution cable GJFJV description

GJFJV multi-purpose distribution cable use several $\phi 900\mu\text{m}$ flame retardant tight buffer fiber as optical communication medium,the tight buffer fiber wrapped with a layer of aramid yarn as strength member units,and the cable is completed with a PVC or LSZH(Low smoke,Zero halogen flame retardant)Sheath.

Application: Multi optical jumper and Indoor any purpose cable distribution

Multi purpose distribution cable GJFJV Characteristics

- 1.Tight buffer fiber ease of stripping
- 2.Aramid yarn as strength member make cable have excellent tensile strength
- 3.The jacket anti-corrosion,waterproof,anti-ultraviolet radiation,flame retardant and harmless to environment etc.
- 4.Product standards:Comply with Standards YD/T 1258.4-2005 、 ICEA-596 、 GR-409 、 IEC 60794-2-20/21, etc, and meet the requirements of UL approval for OFNR.

Multi purpose distribution cable GJFJV Technical parameters

Cable Code	Diameter(mm)	Weight(kg/km)	Tensile strength(Long/Short)N	Crush resistance(Long/Short)N/100mm	Bending radius(Dynamic/Static)	Sheath Material
GJFJV-02	4.1±0.25	12.4	200/660	300/1000	20D/10D	PVC/LSZH
GJFJV-04	4.8±0.25	16.2	200/660	300/1000	20D/10D	PVC/LSZH
GJFJV-06	5.2±0.25	20	200/660	300/1000	20D/10D	PVC/LSZH
GJFJV-08	5.6±0.25	26	200/660	300/1000	20D/10D	PVC/LSZH
GJFJV-10	5.8±0.25	28	200/660	300/1000	20D/10D	PVC/LSZH
GJFJV-12	6.4±0.25	31.5	200/660	300/1000	20D/10D	PVC/LSZH
GJFJV-24	8.5±0.3	42.1	200/660	300/1000	20D/10D	PVC/LSZH

Transport/Storage/Operating Temperature:-20°C~+60°C,Installation temperature:-5°C~+50°C

Multi purpose distribution cable GJFJV Construction

